

CONTAINS NO CBI

Form Approved
OMB No. 2010-0019
Approval Expires 12-31-89

59 AUG -7 AM 8: 34

@ EPA-OTS

90-890000586

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
Comprehensive Assessment Information Rule
REPORTING FORM

When completed, send this form to:

Document Processing Center
Office of Toxic Substances, TS-790
U.S. Environmental Protection Agency
401 M Street, SW
Washington, DC 20460
Attention: CAIR Reporting Office

For Agency Use Only:

Date of Receipt:

Document

Control Number:

Docket Number:

EPA Form 7710-52

PART	A (	GENERAL REPORTING INFORMATION
1.01	Thi	is Comprehensive Assessment Information Rule (CAIR) Reporting Form has been
CBI	con	mpleted in response to the <u>Federal Register</u> Notice of $[\overline{O}]7$ $[\overline{1}]3$ $[\overline{8}]\overline{9}$
[_]	a.	If a Chemical Abstracts Service Number (CAS No.) is provided in the $\underline{Federal}$
		<u>Register</u> , list the CAS No [_]_]_]_]_]_]_]-[_]]
	<b>b.</b>	If a chemical substance CAS No. is not provided in the <u>Federal Register</u> , list either (i) the chemical name, (ii) the mixture name, or (iii) the trade name of the chemical substance as provided in the <u>Federal Register</u> .
		(i) Chemical name as listed in the rule Isocyanate Terminated Polyo
		(ii) Name of mixture as listed in the rule Solithone 5-113:6 to 7%
		(iii) Trade name as listed in the rule Solithone 113/300/112
	c.	If a chemical category is provided in the <u>Federal</u> <u>Register</u> , report the name of the category as listed in the rule, the chemical substance CAS No. you are reporting on which falls under the listed category, and the chemical name of the substance you are reporting on which falls under the listed category.
		Name of category as listed in the rule
		CAS No. of chemical substance
		Name of chemical substance Toluene Diisocyanate
1.02 CBI		entify your reporting status under CAIR by circling the appropriate response(s).
 [_]		orter 2
` <u>_</u> `		cessor .)
		manufacturer reporting for customer who is a processor 4
	X/P	processor reporting for customer who is a processor

1.03	Does the substance you are reporting on have an " $x/p$ " designation associated with it in the above-listed <u>Federal</u> <u>Register</u> Notice?
<u>CBI</u>	Yes Go to question 1.04
	No
1.04 CBI	a. Do you manufacture, import, or process the listed substance and distribute it under a trade name(s) different than that listed in the Federal Register Notice? Circle the appropriate response.
<u>[]</u> ]	Yes
	b. Check the appropriate box below:
	[_] You have chosen to notify your customers of their reporting obligations
	Provide the trade name(s)
	[_] You have chosen to report for your customers
	You have submitted the trade name(s) to EPA one day after the effective date of the rule in the <u>Federal Register</u> Notice under which you are reporting.
1.05	If you buy a trade name product and are reporting because you were notified of your reporting requirements by your trade name supplier, provide that trade name.
CBI	Trade name Solithane 113/300/T12
[_]	Is the trade name product a mixture? Circle the appropriate response.
_	Yes
1.06	Certification The person who is responsible for the completion of this form must sign the certification statement below:
<u>CBI</u>	"I hereby certify that, to the best of my knowledge and belief, all information entered on this form is complete and accurate."  Gary L. Pevkins  NAME  SIGNATURE  DATE SIGNED
	Manager of Facilities (407) 727 - 0660 x-2532 TITLE TITLE
[_] 1	Mark (X) this box if you attach a continuation sheet.

1.07 <u>CBI</u> [_]	Exemptions From Reporting If with the required information on within the past 3 years, and thi for the time period specified in are required to complete section now required but not previously submissions along with your Sect	n a CAIR Reis information the rule in 1 of this submitted	eporting Form for the tion is current, accu , then sign the certi s CAIR form and provi . Provide a copy of	listed substance rate, and complete fication below. You de any information
	"I hereby certify that, to the binformation which I have not income to EPA within the past 3 years a period specified in the rule."	cluded in	this CAIR Reporting F	orm has been submitted
	NAME		SIGNATURE	DATE SIGNED
		( )	_	
	TITLE	` <u> </u>	TELEPHONE NO.	DATE OF PREVIOUS SUBMISSION
1.08 <u>CBI</u> [_]	CBI Certification If you have certify that the following state those confidentiality claims whi "My company has taken measures t and it will continue to take the been, reasonably ascertainable busing legitimate means (other tha judicial or quasi-judicial proinformation is not publicly avaiwould cause substantial harm to	ements true ch you have so protect ese measure by other per an discover deceding) versely	thfully and accuratel we asserted.  the confidentiality es; the information is ersons (other than go ery based on a showin without my company's ewhere; and disclosur	of the information, s not, and has not vernment bodies) by g of special need in consent; the e of the information
	NAME		SIGNATURE	DATE SIGNED
	TITLE	()	TELEPHONE NO.	
	Mark (X) this box if you attach a	oonti	tion about	

PART	B CORPORATE DATA
1.09	Facility Identification
<u>CBI</u>	Name [D]B]A]_ 3 Y 3 T E M 3 \]  0  0  0  0  0  0  0  0  0  0  0  0  0
	[편]린토]인데[편][편][[] [ [ [ [ [ [ [ [ [ [ [ [ [ [ [
	[F][] [3][3][9][5][5][5][5][5][5][5][5][5][5][5][5][5]
	Dun & Bradstreet Number
	Employer ID Number[ <u>중]쿠]⊙]쿠]주]주]주]</u>
	Primary Standard Industrial Classification (SIC) Code
	Other SIC Code[_]_]_]
1.10	Company Headquarters Identification
<u>CBI</u>	Name [\overline{D}\overline{B}\overline{A}\overline{B}\overline{A}\overline{B}\overline{A}\overline{B}
	(円)E1011111111111111111111111111111111111
	[ <u>F]</u> [ <u>3] [ 9] [ 2] - [ 8] [ 5] [ 8]</u> State
	Dun & Bradstreet Number
[_] 1	Mark (X) this box if you attach a continuation sheet.

1.11	Parent Company Identification
<u>CBI</u>	Name [D]B]X]_]S]Y]S]T]E[M]S],]]D]C]_]]_]_]_]_]_]_]_]]]]]]]]]]Address [P]O]_]B]O]X]_]5]5]O]_]]]]]]]]]]]]]]]]]]]]]]]]]]
	(M) E   L   B   O   U   R   N   E   _   _   _   _   _   _   _   _   _
	[F][] [3]2]9]0]2][0]5]5]0] State
	Dun & Bradstreet Number
1.12	Technical Contact
CBI	Name [G]A]R]Y]_]L]_PEIRKIINISI_]_I_I_I_I_I_I_I_I
[_]	Title MIAINIAIGIEIRI IOIFI IFIAICILILILILILILILILILILILILILILILILILIL
	Address [P]D] ] ] [S   O   X   ]   5   5   O   ]   ] ] ] ] ] ] ] ] ] ] ] ] ] ] ]
	MELBOURDE City
	[F]L] [3]2]9]0]2][0]5]5]0] State
	Telephone Number
1.13	This reporting year is from [7]7][8]8] to [7]6][8]9] Mo. Year
	Mark (X) this box if you attach a continuation sheet.

1.14	Facility Acquired If you purchased this facility during the reporting year, provide the following information about the seller:
<u>CBI</u>	Name of Seller [_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]
[_]	Mailing Address [_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]
	[_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]
	[_]_] [_]_]_]_]_][_]_]_]_]_ State
	Employer ID Number
	Date of Sale
	Contact Person [_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]
	Telephone Number
1.15	Facility Sold If you sold this facility during the reporting year, provide the following information about the buyer:
CBI	Name of Buyer [_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]
[_]	Mailing Address [_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]
,	[_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]
	[_]_] [_]_]_]_][_]]]] State Zip
	Employer ID Number
	Date of Purchase
	Contact Person [_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]_]
	Telephone Number
[_] !	Mark (X) this box if you attach a continuation sheet.

C	lassification	Quantity (
_		
M	anufactured	•
Ι	mported	•
P	rocessed (include quantity repackaged)	•
0	f that quantity manufactured or imported, report that quantity:	
	In storage at the beginning of the reporting year	•
	For on-site use or processing	•
	For direct commercial distribution (including export)	•
	In storage at the end of the reporting year	•
0	f that quantity processed, report that quantity:	
	In storage at the beginning of the reporting year	
	Processed as a reactant (chemical producer)	_
	Processed as a formulation component (mixture producer)	
	Processed as an article component (article producer)	
	Repackaged (including export)	
	In storage at the end of the reporting year	. <del>6</del>

or a chemi	re If the l component of a cal. (If the component chem	mixture, mixture co	provide the mposition	ne following is variable	informati	on for e	ach component
	Component Name			Supplier Name		Composi (speci	verage % tion by Weigh fy precision, , 45% ± 0.5%)
Tolu	ene Diisocy	vanate	<u>ABLE</u>	STIK LA	BORATOR	I <u>es</u>	<u> </u>
Ine	ene Diisocy rt Ingred	iants					95%
	W1-4						
<del>`</del>			· <del></del>			Total	100%

2.04	State the quantity of the listed substance that your facility manufactor processed during the 3 corporate fiscal years preceding the report descending order.	etured, imported ting year in
<u>CBI</u>		
[_]	Year ending	<u>                                    </u>
	Quantity manufactured	N/A k
	Quantity imported	N/A h
	Quantity processed	
	Year ending	[ <u>0]6</u> ] [ <u>8]</u> Mo. Year
	Quantity manufactured	/4/A k
	Quantity imported	k
	Quantity processed	<i>N/A</i> k
	Year ending	[ <u>0</u> ] <u>6</u> ] [ <u>8</u> ] <u>4</u> Mo. Year
	Quantity manufactured	<i>N /</i> ∧ k
	Quantity imported	<i>N/A</i> k
	Quantity processed	<i>∧/∧</i> k
2.05 CBI	Specify the manner in which you manufactured the listed substance. C appropriate process types.	ircle all
[_]	Continuous process	•••••
	Semicontinuous process	• • • • • • • • • • • • • • • • • • • •
	Batch process	• • • • • • • • • • • • • • • • • • • •
	·	
[_]	Mark (X) this box if you attach a continuation sheet.	V #

2.06 CBI	Specify the manner in appropriate process ty	which you processed t pes.	the listed substance.	Circle all
[_]	Continuous process	• • • • • • • • • • • • • • • • • • • •	•••••	1
	Semicontinuous process	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	2
_	Batch process	• • • • • • • • • • • • • • • • • • • •		3
				_
2.07 CBI	State your facility's a substance. (If you are question.)	name-plate capacity f e a batch manufacture	for manufacturing or per or batch processor,	rocessing the listed do not answer this
	question.)			
[_]	Manufacturing capacity	• • • • • • • • • • • • • • • • • • • •		kg/yr
	Processing capacity			kg/yr
2.08 CBI	If you intend to increamanufactured, imported, year, estimate the increase volume.	or processed at any	time after your curr	ent corporate fiscal
[_]		Manufacturing Quantity (kg)	Importing Quantity (kg)	Processing Quantity (kg)
	Amount of increase			
	Amount of decrease			
[_]	Mark (X) this box if yo	u attach a continuat	ion sheet.	

2.09	listed substance substance during	argest volume manufacturing or processing proce e, specify the number of days you manufactured g the reporting year. Also specify the average s type was operated. (If only one or two opera	or processed number of h	the listed ours per
<u>CBI</u>				Average Hours/Day
	Process Type #1	(The process type involving the largest quantity of the listed substance.)		
		Manufactured	MIM	N/A
		Processed	4	<u> </u>
	Process Type #2	(The process type involving the 2nd largest quantity of the listed substance.)		
		Manufactured  Processed	NA	N/A
		Processed	<u> </u>	N/A
	Process Type #3	(The process type involving the 3rd largest quantity of the listed substance.)		
		Manufactured	N/A	N/A
		Manufactured  Processed	N/A	N/N
2.10 CBI		um daily inventory and average monthly inventor was stored on-site during the reporting year in	y of the lis the form of	ted a bulk
	Maximum daily in	nventory	•	kg
	Average monthly	inventory	•	kg
	Mark (X) this bo	ox if you attach a continuation sheet.		***************************************

<u>CBI</u>	etc.).	o the product (e.g., ca	irryover from raw	material, reaction	
	CAS No.	Chemical Name	Byproduct, Coproduct or Impurity <sup>1</sup>	Concentration (%) (specify ± % precision)	Source of By products, Coproducts, or Impurities
	B = Byproduct				
	C = Coproduct I = Impurity				
	C = Coproduct				
	C = Coproduct				
	C = Coproduct				
	C = Coproduct				

<u>CBI</u>	imported, or processed using the listed the quantity of listed substance you us total volume of listed substance used of quantity of listed substance used capti- listed under column b., and the types of the instructions for further explanation	se for eduring to lively or of end-	each product type the reporting year n-site as a percen users for each pro	as a percentage of the . Also list the tage of the value		
	a. b. % of Quantit Manufactured Imported, of Product Types <sup>1</sup> Processed	i,	c. % of Quantity Used Captively On-Site	d. Type of End-Users <sup>2</sup>		
	K 100°/0		100%	Н		
	<pre>"Use the following codes to designate procession of the superior of the s</pre>	L = M = N = 0 = Q = R = V = V = V = Lves X =	L = Moldable/Castable/Rubber and ad M = Plasticizer N = Dye/Pigment/Colorant/Ink and ad 0 = Photographic/Reprographic chemi and additives P = Electrodeposition/Plating chemi Q = Fuel and fuel additives R = Explosive chemicals and additiv S = Fragrance/Flavor chemicals T = Pollution control chemicals U = Functional fluids and additives V = Metal alloy and additives W = Rheological modifier X = Other (specify)  ype of end-users:			

2.13 <u>CBI</u> [_]	import, or process usi corporate fiscal year. import, or process for	ng the listed substa For each use, spece each use as a perce the reporting year. as a percentage of each product type.	nce at any time after ify the quantity you ntage of the total was also list the quantithe value listed under the value listed under the second control of	n expect to manufacture, volume of listed city of listed substance der column b., and the
	a.	b.	с.	d.
	Product Types <sup>1</sup>	% of Quantity Manufactured, Imported, or Processed	% of Quantity Used Captively On-Site	Type of End-Users <sup>2</sup>
	K	1000/0	100%	<u> </u>
	A = Solvent B = Synthetic reactant C = Catalyst/Initiator/Accelerator Sensitizer D = Inhibitor/Stabilizer/Scavenger Antioxidant E = Analytical reagent F = Chelator/Coagulant/Sequestrant G = Cleanser/Detergent/Degreaser H = Lubricant/Friction modifier/Aragent I = Surfactant/Emulsifier J = Flame retardant K = Coating/Binder/Adhesive and accelerations		L = Moldable/Castal M = Plasticizer N = Dye/Pigment/Col O = Photographic/Re and additives P = Electrodepositi Q = Fuel and fuel a R = Explosive chemi S = Fragrance/Flavo T = Pollution conti U = Functional flui V = Metal alloy and W = Rheological mod X = Other (specify) type of end-users:	icals and additives or chemicals col chemicals ids and additives i additives
	I = Industrial CM = Commercial		r (specify) <u> V  L 7</u>	TARY_
[_]	Mark (X) this box if yo	ou attach a continua	tion sheet.	

a.	b.	c. Average % Composition of	d.
Product Type <sup>1</sup>	Final Product's Physical Form <sup>2</sup>	Listed Substance in Final Product	Type of End-Users <sup>3</sup>
<u> </u>	F 2		₩
<sup>1</sup> Use the following	codes to designate pro	oduct types:	<b></b>
A = Solvent		L = Moldable/Castable	/Rubber and addit:
B = Synthetic read		M = Plasticizer	
C = Catalyst/Init:	iator/Accelerator/	N = Dye/Pigment/Color	
Sensitizer D = Inhibitor/Stab	milizor/Soovongor/	<pre>0 = Photographic/Repr     and additives</pre>	ographic chemical
Antioxidant	Jiiizei/ Scavengei/	P = Electrodeposition	/Plating chemical
E = Analytical rea	agent	Q = Fuel and fuel add	
F = Chelator/Coagu		R = Explosive chemica	
G = Cleanser/Deter		S = Fragrance/Flavor	
	tion modifier/Antiwear		
agent		U = Functional fluids	and additives
I = Surfactant/Emu		V = Metal alloy and a	
J = Flame retardar		W = Rheological modif	ier
_	:/Adhesive and additive		
Use the following A = Gas		e final product's physic stalline solid	al form:
B = Liquid	F3 = Grain		
C = Aqueous soluti	on $F4 = 0th$	er solid	
D = Paste	G = Gel		
E = Slurry	H = Oth	er (specify)	
F1 = Powder  3 Use the following	codes to designate the	type of end-users:	
I = Industrial	CS - Con	Slimer	
CM = Commercial	H = 0th	er (specify) MILITA	1RY
		-	

[] (		ed substance to off-site customers.		1
'_'`		car		
		e, Vessel		
	_	line		
		e		
	otnei	(specify)		
2.16 CBI	or pr	omer Use Estimate the quantity of the listed substance repared by your customers during the reporting year for used use listed (i-iv).		
[_]	Cate	gory of End Use		
	i.	Industrial Products		
		Chemical or mixture	N/A	kg/yr
		Article	0.01	kg/yr
	ii.	Commercial Products		
		Chemical or mixture	N/A	kg/yr
		Article	N/A	kg/yr
	iii.	Consumer Products	•	
		Chemical or mixture	N/X	kg/yr
		Article	N/A	kg/yr
	iv.	<u>Other</u>	, ,	
		Distribution (excluding export)	NA	kg/yı
		Export	NIA	kg/yr
		Quantity of substance consumed as reactant	NIA	kg/yı
		Unknown customer uses	NIA	kg/yr

# SECTION 3 PROCESSOR RAW MATERIAL IDENTIFICATION

	A GRANDAL DAGA	· · · · · · · · · · · · · · · · · · ·								
PART	A GENERAL DATA									
3.01 <u>CBI</u>	Specify the quantity purchased and the average price paid for the listed substance for each major source of supply listed. Product trades are treated as purchases. The average price is the market value of the product that was traded for the listed substance.									
l1	Source of Supply	Quantity (kg)	Average Price (\$/kg)							
	The listed substance was manufactured on-site.	A/A	N/n							
	The listed substance was transferred from a different company site.	N/A	N/A							
	The listed substance was purchased directly from a manufacturer or importer.	0./	\$50,00							
	The listed substance was purchased from a distributor or repackager.	N/n	NIA							
	The listed substance was purchased from a mixture producer.	N/A	N/A							
3.02	Circle all applicable modes of transportation used to	dolivor the lie	****************							
CBI	your facility.	deliver the lis	ted substance to							
,_,(	Truck									
	Railcar	• • • • • • • • • • • • • • • • • • • •	2							
	Barge, Vessel		_							
	Pipeline									
(	Plane									
	Other (specify)	• • • • • • • • • • • • • • • • • • • •	6							
_l	Mark (X) this box if you attach a continuation sheet.									
	A Particular Control of the Control	7 - W								

3.03 <u>CBI</u>	a.	Circle all applicable containers used to transport the listed substance to you facility.	r
[_]		Bags  Boxes	
		Free standing tank cylinders	
		Tank rail cars	
		Hopper cars	
		Tank trucks	. 6
		Hopper trucks	. 7
		Drums	. 8
		Pipeline	. 9
		Other (specify)	.10
	b.	If the listed substance is transported in pressurized tank cylinders, tank rai cars, or tank trucks, state the pressure of the tanks.	1
		Tank cylinders mm	mHg
		m 1 13	mHg
			mHg
[_]	Mark	k (X) this box if you attach a continuation sheet.	

3.04 <u>BI</u>	If you obtain the listed substance in the form of a mixture, list the trade name(s) of the mixture, the name of its supplier(s) or manufacturer(s), an estimate of the average percent composition by weight of the listed substance in the mixture, and the amount of mixture processed during the reporting year.							
	Trade Name	Supplier or Manufacturer	Average % Composition by Weight (specify ± % precision)	Amount Processed (kg/yr)				
		•						

.05 <u>31</u> 	State the quantity of the listed substance used as a raw material during the reporting year in the form of a class I chemical, class II chemical, or polymer, and the percent composition, by weight, of the listed substance.							
<b></b> •		Quantity Used (kg/yr)	% Composition by Weight of Listed Substance in Raw Material (specify $\pm$ % precision					
	Class I chemical							
	Class II chemical							
	Polymer	· · · · · · · · · · · · · · · · · · ·						
		<del></del>	<del></del>					
			· · · · · · · · · · · · · · · · · · ·					

SECTION	٨.	PHYSTCAL/CHEMICAL	DDUDEDALEC
SELLI LUIV	4	PRISILAL/URBMICAL	PRUPERLIES

c	en	۵	ra	1	T	n	0	r	rı	1	^	t	i	n.	n	C	•	

If you are reporting on a mixture as defined in the glossary, reply to questions in Section 4 that are inappropriate to mixtures by stating "NA -- mixture."

For questions 4.06-4.15, if you possess any hazard warning statement, label, MSDS, or other notice that addresses the information requested, you may submit a copy or reasonable facsimile in lieu of answering those questions which it addresses.

iacsi	mile in fleu of answering	those questions whic	n it addresses.						
PART	A PHYSICAL/CHEMICAL DATA	SUMMARY							
4.01 <u>CBI</u>	Specify the percent purity for the three major 1 technical grade(s) of the listed substance as it is manufactured, imported, or processed. Measure the purity of the substance in the final product form for manufacturing activities, at the time you import the substance, or at the point you begin to process the substance.								
· ,		Manufacture	<u>Import</u>	Process					
	Technical grade #1	% purity	% purity	<u>95</u> % purity					
	Technical grade #2	% purity	% purity	% purity					
	Technical grade #3	% purity	% purity	% purity					
	<sup>1</sup> Major = Greatest quanti	ty of listed substanc	e manufactured, importe	ed or processed.					
4.02	Submit your most recently updated Material Safety Data Sheet (MSDS) for the listed substance, and for every formulation containing the listed substance. If you possess an MSDS that you developed and an MSDS developed by a different source, submit your version. Indicate whether at least one MSDS has been submitted by circling the appropriate response.  Yes								
,									
	No			2					
	Indicate whether the MSDS	S was developed by yo	ur company or by a diff	ferent source.					
	Your company	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •						
(	Another source			2					

[ ] Mark (X) this box if you attach a continuation sheet.

# MATERIAL SAFETY DATA SHEET

## 1. PRODUCT IDENTIFICATION

TRADE NAME: Solithane 113/300/T12

CHEMICAL NAMES: Isocyanate Terminated Polyol

MANUFACTURER'S NAME: ABLESTIK LABORATORIES

ADDRESS:

833 West 182nd Street, Gardena, CA 90248 (213) 532-9341

REVISION DATE: 01/11/89

II HAZARDOUS INGREDIENTS

**PERCENT** CAS NUMBERS **EXPOSURE LIMIT** 

ACGIH(TWA)

OSHA(PEL)

Toluene diisocyanate

CHEMICAL NAMES

584-84-9

0.005ppm

MELTING POINT(°F): Not applicable

BOILING POINT (°F @ 760 mm Hg): 482°

PERCENT VOLATILE BY VOLUME: < 6

< 5

0.02ppm

**III PHYSICAL PROPERTIES** 

VAPOR DENSITY (AIR=1): > 1

SPECIFIC GRAVITY: 1.2

SOLUBILITY IN WATER: Not applicable

VAPOR PRESSURE, mm Hg at 20°C: < 0.1 EVAPORATION RATE (ETHER =1): < 1

APPEARANCE AND ODOR: Pale yellow liquid; pungent odor

IV FIRE AND EXPLOSION

FLASH POINT, °F (GIVE METHOD): 200° (Setaflash) AUTOIGNITION TEMPERATURE: Not determined

FLAMMABLE LIMITS IN AIR, VOLUME %: LOWER Not determined UPPER Not determined

FIRE EXTINGUISHING MATERIALS: Dry chemical, foam.

FIRE EXTINGUISHING PROCEDURES: Wear self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Protect against inhalation of cyanate vapors and other

decomposition/combustion products.

**HEALTH HAZARD INFORMATION** SYMPTOMS OF OVEREXPOSURE FOR EACH POTENTIAL ROUTE OF EXPOSURE

INHALED: Unknown for product mixture. Inhalation of isocyanate vapors can produce severe irritation of the mucous membranes in the respiratory tract, i.e. nose, throat, and lungs. Exposure of humans to concentrations of isocyanate vapor in excess of the maximum acceptable concentration has caused illness characterized by breathlessness, chest discomfort and reduced pulmonary function. Massive exposure to high concentrations has caused, within minutes, irritation of the trachea and larynx and severe coughing spasms. Concentrations of isocyanate vapors should be maintained below the TLV by engineering controls. Can cause sensitization in humans. TDI Inhalation-Human TCLo: 0.02ppm/2Y:PUL. TDI Inhalation-Human TCLo: 0.5ppm: IRR. Symptoms of overexposure may be

delayed and could include dry cough, chest tightness, wheezing, shortness of breath, asthmatic type symptoms

CONTACT WITH SKIN: Unknown for product mixture. Isocyanates react with skin protein and tissue moisture. If not promptly removed, liquid spills on the skin can cause reddening, swelling, and blistering of exposed skin. REPEATED SKIN CONTACT HAS CAUSED SKIN SENSITIZATION IN HUMANS AND SHOULD BE AVOIDED. TDI: Skin-Rabbit: 500 mg/24H MOD. Overexposure may cause irritation, dermatitis and possible skin sensitization given prolonged or repeated skin contact.

CONTACT WITH EYES: Unknown for the mixture. Liquid isocyanates splashed into the eyes can be harmful to the delicate eye tissue and must be avoided. Injury results from reaction of the isocyanate with the eye fluid which may dehydrate the tissue and result in severe imitation of the eyelid and possible damage to the cornea (corneal opacity). Exp

to high concentrations of isocyanate vapor can lead to formation of solid crystals in the eye fluid causing mechanical imitation of the eyes hours after exposure. TDI Eye-Rabbit: 100 mg SEV. Overexposure can cause irritation, tearing, reddening and blurred vision.

ABSORBED THROUGH SKIN: Isocyanates react with skin protein and tissue moisture. Absorption through skin may be harmful.

SWALLOWED: Unknown for the mixture. Animal experiments indicate that the toxic effects of TDI or polymeric isocyanates, when ingested, are slight. The LD50 in rats for TDI is 5840 mg/kg. From these experiments, it is believed that ingestion of TDI or polymeric isocyanates would not be fatal to humans, but could result in irritation and corrosive action on the mouth and stomach tissue. Overexposure may cause nausea, vomiting, and gastrointestinal pain.

#### HEALTH EFFECTS OR RISKS FROM EXPOSURE:

**ACUTE**: See symptoms of overexposure, section V.

CHRONIC: Unknown for product mixture. Toluene Diisocyanate(TDI) is considered a suspect carcinogen as tested by National Toxicology Program, 1983, in rats and female mice. Administered by gavage to rats, TDI caused subcutaneous neoplasms or cancers in both sexes. Additionally, males developed pancreatic neoplasms and females pancreatic, liver and mammary neoplasms. In mice similarly exposed, TDI caused circulatory neoplasms and cancers (combined) and liver neoplasms in females but was not carcinogenic to males. (NTP 1983 Program Tech Report on Carcinogenic Study of Commercial Grade of TDI.)

#### FIRST AID: EMERGENCY PROCEDURE

EYE CONTACT: Immediately flush with water for 15 minutes lifting the upper and lower eyelids occasionally and obtain immediate medical attention.

SKIN CONTACT: Wash immediately with soap and water. If imitation persists, seek medical attention immediately

INHALED: Remove to fresh air immediately. Administer artificial respiration as required. Obtain medical attention. INGESTION: Do not induce vomiting. Obtain immediate medical attention. If unavailable, contact nearest Poison Control Center.

SUSPECTED CANCER AGENT? Toluene diisocyanate is considered to be carcinogenic by NTP.

		VI REAC	TIVITY DATA	
STABILITY:	X STABLE	UNSTABLE		
CONDITIONS TO	AVOID: Heat prior to	o cure.		
<b>INCOMPATIBILIT</b>	TY (MATERIALS TO	AVOID): Moisture,	strong oxidizing age	nts
HAZARDOUS DE	ECOMPOSITION PRO	ODUCTS (INCLUDI	NG COMBUSTION F	PRODUCTS):
HAZARDOUS PO	e, carbon dioxide, nit LYMERIZATION: _ DAVOID: None know	MAY OCCUR		des, and hydrogen cyanide OCCUR

#### VII SPILL, LEAK AND DISPOSAL

SPILL RESPONSE PROCEDURES: Wipe up with solvent saturated toweling and collect in an appropriate container for disposal.

PREPARING WASTES FOR DISPOSAL: Dispose in approved chemical disposal area or in a manner which complies with all local, state and federal regulations.

#### VIII SPECIAL HANDLING INFORMATION

VENTILATION AND ENGINEERING CONTROLS: Provide adequate ventilation to minimize inhalation. Mechanical (local exhaust) recommended for all spray operations and elevated temperature uses.

RESPIRATORY PROTECTION: Wear NIOSH-MSHA approved self-contained positive pressure breathing apparatus as necessary within equipment limitations. Contaminant levels will vary dependent on the operation.

EYE PROTECTION: Safety goggles with side shields.

GLOVES: Rubber

OTHER CLOTHING AND EQUIPMENT: Protective equipment to cover exposed areas.

WORK PRACTICES, HYGIENIC PRACTICES: Vent curing oven to outdoors.

OTHER HANDLING AND STORAGE REQUIREMENTS: Store frozen at all times.

PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:

Avoid contact with skin, eyes and clothing. Good housekeeping is required. Avoid inhalation of vapors.

#### IX REGULATORY INFORMATION

#### SARA/TITLE III - TOXIC CHEMICALS LIST:

This product contains chemicals subject to the reporting requirements of section 313 of Title III of Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

< 5

584-84-9

Toluene diisocyanate

#### TSCA INVENTORY STATUS:

Chemical components listed on TSCA Inventory

## **CALIFORNIA PROPOSITION 65:**

This product does not contain toxic chemicals currently on the California List of known carcinogens and reproductive toxins.

DISCLAIMER: THE INFORMATION GIVEN AND THE RECOMMENDATIONS MADE HEREIN APPLY TO OUR PRODUCT(S) ALONE AND NOT IN COMBINATION WITH ANY OTHER PRODUCT(S). SUCH INFORMATION AND RECOMMENDATIONS ARE BASED ON OUR RESEARCH AND ON DATA FROM OTHER RELIABLE SOURCES AND ARE BELIEVED TO BE ACCURATE BUT NO GUARANTEE OF THEIR ACCURACY IS MADE. IN EVERY CASE WE URGE AND RECOMMEND THAT PURCHASERS BEFORE USING ANY PRODUCT MAKE THEIR OWN TESTS TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS AND TO DETERMINE TO THEIR OWN SATISFACTION WHETHER THE PRODUCT IS SUITABLE FOR THEIR PARTICULAR PURPOSES. THE PRODUCT(S) DISCUSSED HEREIN ARE SOLD WITHOUT ANY WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED.

# MORTON THIOKOLING

Morton Chemical Division



# **Material Safety Data Sheet**

SECTION I:

PRODUCT IDENTIFICATION

PRODUCT NAME:

CHEMICAL NAME:

COMMON NAME:

Isocyanate Terminated Polyol Isocyanate Terminated Polyol

CAS NUMBER:

PRODUCT USE:

Coatings and Castings

EMERGENCY PHONE:

815-338-1800 (24 hours/day)

OTHER EMERGENCY PHONE:

312-807-3142

EFFECTIVE DATE: SUPERSEDES:

December, 1987 October 15, 1986

SECTION II:

HAZARDOUS INGREDIENTS

CHEMICAL NAME/COMMON NAME Toluene Diisocyanate TDI

CAS NO. 584-84-9 OSHA PEL 2

ACCIH/TLV

0.02ppm 0.005ppm 0.02ppm

1 Typical amount, not a specification

2 Governed by a ceiling limit value (c) - The value which should not be exceeded even instantaneously.

#### SECTION III:

#### PHYSICAL DATA

BOILING POINT (760 mm Hq):

482 degrees F (250 degrees C)

SPECIFIC GRAVITY (Water = 1):

1.073

VAPOR PRESSURE (mm Hq):

Not applicable

VAPOR DENSITY (Air=1):

> 6

% NONVOLATILE:

93

pH:

Not applicable

EVAPORATION RATE (Ether=1):

< 1

SOLUBILITY IN WATER:

Not applicable

APPEARANCE:

Pale Yellow

ODOR:

Irritating Pungent Odor

#### SECTION IV:

#### FIRE AND EXPLOSION DATA

FLASH POINT: > 200 degrees F

FLAMMABLE LIMITS Lel: Not Applicable

(> 94 degrees C)

<u>Uel:</u> Not Applicable

METHOD USED: SETAFLASH

EXTINGUISHING MEDIA: Foam, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Fire fighters should wear NIOSH/MSHA approved self-contained positive pressure breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None as far as known.

HAZARDOUS DECOMPOSITION PRODUCTS: If burned, gives off carbon monoxide, carbon dioxide, nitrogen oxides, aromatic amines, aldehydes, and hydrogen cyanide.

S-113 Page 1 of 5

ORAL TOXICTTY: Unknown for product mixture. Animal experiments indicate that the toxic effects of TDI or polymeric isocyanates, when ingested, are slight. The ID50 in rats for TDI is 5840mg/Kg. From these experiments, it is believed that ingestion of TDI or polymeric isocyanates would not be fatal to humans, but could result in irritation and corrosive action on the mouth and stomach tissue. See 3

<u>DERMAL TOXICITY:</u> Unknown for product mixture. Isocyanates react with skin protein and tissue moisture. If not promptly removed, liquid spills on the skin can cause reddening, swelling, and blistering of exposed skin. REPEATED SKIN CONTACT HAS CAUSED SKIN SENSITIZATION IN HUMANS AND SHOULD BE AVOIDED.

TDI: Skin-Rabbit: 500 mg/24H MOD See Note 3

EYE TOXICITY: Unknown for product mixture. EYE CONTACT - LIQUID ISOCYANATES SPLASHED INTO THE EYES CAN BE HARMFUL TO THE DELICATE EYE TISSUE AND MUST BE AVOIDED. Injury results from reaction of the isocyanate with the eye fluid which may dehydrate the tissue and result in severe irritation of the eyelid and possible damage to the cornea (corneal opacity). Exposure to high concentrations of isocyanate vapor can lead to formation of solid crystals in the eye fluid causing mechanical irritation of the eyes hours after exposure. TDI Eye-Rabbit: 100 mg SEV See Note 3

INHALATION TOXICITY: Unknown for product mixture. Inhalation of isocyanate vapors can produce severe irritation of the mucous membranes in the respiratory tract, i.e. nose, throat, and lungs. Exposure of humans to concentrations of isocyanate vapor in excess of the maximum acceptable concentration has caused illness characterized by breathlessness, chest discomfort and reduced pulmonary function. Massive exposure to high concentrations has caused, within minutes, irritation of the trachea and larynx and severe coughing spasms. Massive exposure may also lead to bronchitis, bronchial spasm, and/or pulmonary edema (chemical pheumonitis). Concentrations of isocyanate vapors should be maintained below the TIV by engineering controls. Can cause sensitization in humans.

TDI Inhalation-Human TCLO: 0.02 ppm/2Y:PUL See Note 3
TDI Inhalation-Human TCLO: 0.5 ppm:IRR See Note 3

CHRONIC TOXICITY: Unknown for product mixture. Toluene Diisocyanate (TDI) is considered a suspect carcinogen as tested by National Toxicology Program, 1983, in rats and female mice. Administered by gavage to rats, TDI caused subcutaneous neoplasms or cancers in both sexes. Additionally, males developed pancreatic neoplasms and females pancreatic, liver and mammary neoplasms. In mice similarly exposed, TDI caused circulatory neoplasms and cancers (combined) and liver neoplasms in females but was not carcinogenic to males. (NTP 1983 Program Tech Report on Carcinogenic Study of Commercial Grade of TDI.)

# **EFFECTS OF OVEREXPOSURE:**

INGESTION:

Not established for product mixture. Possible nausea, vomiting, and gastrointestinal pain.

SKIN CONTACT:

Not established for product mixture. May cause irritation, dermatitis and possible skin sensitization given prolonged or repeated skin contact.

3 R.T.E.C.S. 1981-82 CZ6300000

EYE CONTACT:

Not established for product mixture. Possible irritation, tearing, reddening and blurred

vision.

INHALATION:

Not established for product mixture. Possible

respiratory tract, mucous membrane

irritation, sensitization. Symptoms may be delayed and could include dry cough, chest tightness, wheezing, shortness of breath,

asthmatic type symptoms.

ACUTE SYSTEMIC:

Overexposure may cause irritation of the eyes, nose and throat. Severe overexposure

may cause weakness, drowsiness, and

unconsciousness.

CHRONIC SYSTEMIC:

Signs and symptoms from chronic exposure resemble those from acute mishaps but are in part systemically more severe. Extended

exposure to isocyanates can cause

sensitization resulting in asthmatic type

symptoms.

NOTES: Toxicity testing on the product mixture has not been conducted.

Comments listed in HEALTH HAZARD DATA pertain to the isocyanate listed in HAZARDOUS INGREDIENTS.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE: Persons with preexisting skin disorders may be more susceptible to isocyanate. In persons with impaired pulmonary function, especially those with obstructive airway diseases, the breathing of isocyanate vapors may cause exacerbation of symptoms due to irritant properties of the isocyanate.

SECTION VI: EMERGENCY HEALTH AND FIRST AID PROCEDURES

EYE CONTACT: Immediately flush with water for 15 minutes lifting the apper and lower eyelids occasionally and obtain immediate medical attention.

SKIN CONTACT: Remove contaminated clothing. Wash exposed areas thoroughly with soap and water. Wash contaminated clothing thoroughly before reuse. If irritation is present after washing, get medical attention.

INHALATION: Move to an area with fresh air and free from risk of further exposure. Administer artificial respiration as required. Obtain medical attention.

INCESTION: Do not induce vomiting. Obtain immediate medical attention. If unavailable, contact nearest Poison Control Center.

NOTE TO PHYSICIAN: May cause weakness, drowsiness, unconsciousness, irritation of eyes, nose and throat, nausea, possible sensitization, coughing, tightness of chest (TDI). No known antidote. Supportive therapy is recommended. Careful lavage may be indicted after ingestion.

SECTION VII:

REACTIVITY DATA

STABILITY: Stable under ordinary storage conditions.

HAZARDOUS CONDITIONS TO AVOID: Storage at temperatures above 110 degrees F (43 degrees C) and moisture contact.

INCOMPATIBILITY: (MATERIALS TO AVOID) Oxidizing substances.

CAN HAZARDOUS POLYMERIZATION OCCUR: No.

HAZARDOUS DECOMPOSITION PRODUCTS AND CONDITIONS: If burned, gives off carbon monoxide, carbon dioxide, nitrogen oxides, aromatic amines, aldehydes, and hydrogen cyanide.

SECTION VIII:

SPILL OR LEAK PROCEDURES

RESPONSE TO SPILLS: Stop discharge and contain spill or contaminated material using dike, barrier or other means. Recover with pumping equipment, vacuum truck, sorbent vermiculite or other means. Place contaminated material in suitable container(s) for further handling.

HAZARDS TO BE AVOIDED: Do not flush into stream, other bodies of water or storm sewer. Avoid contact with skin or clothing. Other hazards see Section IV FIRE AND EXPLOSION DATA and Section V HEALTH HAZARD DATA.

SPILL NOTIFICATION: Check Fodorn and Other hazards see

SPILL NOTIFICATION: Check Federal and State reporting regulations.

# DISPOSAL METHODS:

1 Recycle if feasible.

2 Incinerate at authorized facility.

3 Treatment at industrial or liquid treatment facility.

4 Landfill after solidification in a facility authorized to receive waste.

NOTE: THIS MATERIAL, IF BEING DISCARDED, SHOULD BE DISPOSED OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

SECTION IX:

#### CONTROL MEASURES

RESPIRATORY PROTECTION: Wear NIOSH-MSHA approved self-contained positive pressure breathing apparatus as necessary within equipment limitations. Comply with OSHA 1910.134 (CFR), respiratory protection. Contaminant levels will vary dependent on the operation. Industrial hygiene consultation is recommended to assist in respirator selection, use and training.

FOR HANDS, BODY: Chemical resistant gloves recommended for hand protection, work clothing for general body protection.

FOR EYES: Wear safety glasses, chemical goggles or face shield (eight inch minimum).

<u>VENITIATION:</u> Provide adequate ventilation to minimize inhalation.

Mechanical (local exhaust) recommended for all spray operations and elevated temperature uses.

SECTION X:

#### SPECIAL PRECAUTIONS

RECOMMENDED STORAGE PRACTICE AND CONDITIONS: Store between 50 and 100 degrees F (10 and 38 degrees C). Storage at higher temperatures causes polymerization.

OTHER PRECAUTIONS: For industrial use only. Eye wash and shower should be available. Use only under well ventilated conditions. For personal hygiene protection, personnel should wash thoroughly after handling product. Always wash up before eating, smoking, or using washroom facilities. Do not breathe vapor. Do not contact eyes, skin, and or clothing.

SECTION XI:

# LABELING INFORMATION

DOT SHIPPING NAME:

Not regulated by DOT

DOT IDENTIFICATION NO.:

Not applicable

DOT LABEL:

Not applicable

MORTON PRECAUTIONARY LABEL:

177

#### SECTION XII:

# USER'S RESPONSIBILITY

A bulletin such as this cannot be expected to cover all possible situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where, precautions in addition to those described herein, are required. Any health hazard and safety information contained herein should be passed on to your customers or employees, as the case may be. Morton Thiokol, Inc. must rely on the user to utilize the information we have supplied to develop work practice guidelines and employee instructional programs for the individual operation.

# DISCLAIMER OF LIABILITY

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical is the sole responsibility of the user. Users of any chemical should satisfy themselves that the conditions and methods of use assure that the chemical is used safely. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN OR THE CHEMICAL TO WHICH THE INFORMATION REFERS. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

Nothing contained herein is to be construed as a recommendation for use in violation of any patents or of applicable laws or regulations.

Morton Thiokol, Inc. Morton Chemical Division 333 West Wacker Drive Chicago, Illinois 60606-1292 (312) 807-2000

been submitted by circling the	appropriate	response.			has 1
					1
No		• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • •		2
corresponding to each physical listed. Physical states for i the time you import or begin t	state of the mporting and poprocess the	listed subsprocessing a listed subs	stance durir activities a stance. Phy	ng the activit are determined vsical states	y at for
		Phys	sical State		
Activity	Solid	Slurry	Liquid	Liquified Gas	Gas
Manufacture	1	2	3	4	5
Import	1	2	3	4	5
Process		2	3	4	5
Store		2	3	4	5
Dispose	$\widetilde{1}$	2	3	4	5
Transport		. 2	3	4	5
	formulation containing the list been submitted by circling the Yes	formulation containing the listed substance been submitted by circling the appropriate of the submitted substance.  Yes	formulation containing the listed substance. Indicate been submitted by circling the appropriate response.  Yes	formulation containing the listed substance. Indicate whether the been submitted by circling the appropriate response.  Yes	For each activity that uses the listed substance, circle all the applicable num corresponding to each physical state of the listed substance during the activit listed. Physical states for importing and processing activities are determined the time you import or begin to process the listed substance. Physical states manufacturing, storage, disposal and transport activities are determined using final state of the product.    Physical State

4.05 <u>CBI</u> []	following percentage particles importing listed su	Size If the lister activities, indicate ge distribution of the size with the size w	e for each ap le listed subs leter. Measur vities at the le physical st	plicable tance by e the ph time yo ate and	physical activity ysical st u import particle	state Do nate and or beging sizes	the size ot includ particle n to proc or manufa	and the e sizes for ess the cturing
	Physical State		Manufacture	Import	Process	Store	Dispose	Transport
	Dust	<1 micron						
		1 to <5 microns						
		5 to <10 microns						
	Powder	<1 micron						<del></del>
		1 to <5 microns						
		5 to <10 microns						·
	Fiber	<1 micron						
		1 to <5 microns		<del></del>				
		5 to <10 microns						
	Aerosol	<1 micron						
		1 to <5 microns						
		5 to <10 microns		<del></del>				
ı—,	Mark (V)	this box if you atta	ch a continue	tion sho	et.			

RT A	A R	ATE CONSTANTS AND TRANSFORMATION PRODUCTS	
)1	Ind	icate the rate constants for the following transformation processes.	
	a.	Photolysis:	
		Absorption spectrum coefficient (peak) $N/A$ (1/M cm) at	nm
		Reaction quantum yield, 6	nm
		Direct photolysis rate constant, $k_p$ , at $N/A$ 1/hr	latitud
	b.	Oxidation constants at 25°C:	
		For <sup>1</sup> 0 <sub>2</sub> (singlet oxygen), k <sub>ox</sub>	1/M
		For RO <sub>2</sub> (peroxy radical), k <sub>ox</sub>	1/M
	c.	Five-day biochemical oxygen demand, BOD <sub>5</sub> N/A	
	d.	Biotransformation rate constant:	
		For bacterial transformation in water, $k_b \dots M/M$	1/hı
		Specify culture $N/N$	
	e.	Hydrolysis rate constants:	
		For base-promoted process, $k_B$	1/M
		For acid-promoted process, $k_A \dots N/A$	1/M
		For neutral process, k <sub>N</sub>	1/h:
:	f.	Chemical reduction rate (specify conditions) $N/A$	<del></del>
s	g.	Other (such as spontaneous degradation) $N/P$	

PART	<b>B</b> 1	PARTITION COEFFICIEN	TS					
5.02	a.	Specify the half-life of the listed substance in the following media.						
		<u>Media</u>			Half-lif	e (speci	y units	)
		Groundwater		N/N				
		Atmosphere		N/A				
		Surface water		N/A				
		Soil						
	b.	Identify the listed life greater than 2	i substance 24 hours.	e's known tr	ansformation	products	that h	ave a half-
		CAS No.		Name	Half-l (specify			Media
							in	<u>cu.tu</u>
							in	
							in	
							in	
5.03		cify the octanol-wat						<u> </u>
5.04	Spe	cify the soil-water	partition	coefficient	, K <sub>d</sub>	N/N		at 25°0
	Soi	l type	• • • • • • • • •	• • • • • • • • • • •	• • • • • • • • • • •			
5.05	Spec	cify the organic car fficient, K <sub>oc</sub>	bon-water	partition	•••••	N/N		at 25°C
5.06	Spec	cify the Henry's Law	Constant,	н	••••••	N/A		atm-m³/mole
	Mark	c (X) this box if you	u attach a	continuatio	on sheet			

Bioconcentration Factor	Species	$\frac{\text{Test}^1}{N/\Lambda}$
N/A	ν/χ	
<sup>1</sup> Use the following codes	to designate the type of test:	
<pre>F = Flowthrough S = Static</pre>		

[_]		Outampière C-13	Total Calas			
	Market	Quantity Sold or Transferred (kg/yr)	Total Sales Value (\$/yr)			
	Retail sales					
	Distribution Wholesalers					
	Distribution Retailers					
	Intra-company transfer					
	Repackagers					
	Mixture producers					
	Article producers					
	Other chemical manufacturers or processors		·			
	Exporters					
	Other (specify)					
			·····			
6.05 <u>CBI</u>	Substitutes List all known commercially feasible substitutes that you know exist for the listed substance and state the cost of each substitute. A commercially feasible substitute is one which is economically and technologically feasible to use in your current operation, and which results in a final product with comparable performance in its end uses.					
[]	Substitute		Cost (\$/kg)			
	NONE					

### SECTION 7 MANUFACTURING AND PROCESSING INFORMATION

### General Instructions:


For questions 7.04-7.06, provide a separate response for each process block flow diagram provided in questions 7.01, 7.02, and 7.03. Identify the process type from which the information is extracted.

## PART A MANUFACTURING AND PROCESSING PROCESS TYPE DESCRIPTION

7.01 In accordance with the instructions, provide a process block flow diagram showing the major (greatest volume) process type involving the listed substance.

CBI

[] Process type ...... APPLICATION OF THERMAL ADHESIVE



7.03	In accordance with the instructions, process emission streams and emission which, if combined, would total at letreated before emission into the environment of the environment of the process type, provide a process type, provide a process type, provide a process block flow diblock.	n points that east 90 perce ironment. If cess block fl sions are rel	t contain t ent of all f all such low diagram leased from	he listed su facility emi emissions ar using the i more than o	bstance and ssions if not e released nstructions ne process
CBI					
[_]	Process type				
	NIA				
				•	
	Mark (X) this how if you attach a con	tinuation sh		****	
iJ	Mark (X) this box if you attach a con	tinuation sh	eet.		

7.04	process block	typical equipment types tillow diagram(s). If a cess type, photocopy this	process block flow	diagram is pro	vided for more
CBI	process type.				
[_]	Process type				
	Unit Operation ID Number 7 A 78	Typical Equipment Type FREEZER  PARTIC SIRINGE	Operating Temperature Range (°C)  -40°C  -40°C	Operating Pressure Range (mm Hg)	Vessel Composition STRIFFSTT
	<u>7C</u>	OVER	20 to 400 %	Amg	STANLECTSTE
				<del></del>	···········
				·	
	Mark (X) this	box if you attach a con	tinuation sheet.		700 M. ATA PARA PARA PARA PARA PARA PARA PARA

7.05	process block flow dia	stream identified in your pagram is provided for more to it separately for each product.	than one process type	agram(s). If a , photocopy this
CBI				
[_]	Process type	N/A		
	Process Stream ID Code	Process Stream Description	Physical State <sup>1</sup>	Stream Flow (kg/yr)
		<del></del>		
	GC = Gas (condensible GU = Gas (uncondensib SO = Solid SY = Sludge or slurry AL = Aqueous liquid OL = Organic liquid	es to designate the physica at ambient temperature and le at ambient temperature a	pressure) nd pressure)	
			·	
[_]	Mark (X) this box if yo	ou attach a continuation she	eet.	


CBI	this questions	on and complete it sepa s for further explanati	rately for each pontion and an example	process type. (	Refer to the
<u>, — , </u>			on and an example	.,	
( <u> </u>	Process type	· · · · · · · · · · · · · · · · · · ·		_	
	<b>a.</b>	b.	с.	d.	е.
	Process Stream ID Code	Known Compounds	Concen- trations <sup>2,3</sup> (% or ppm)	Other Expected Compounds	Estimated Concentrations (% or ppm)
					<del></del>
.06	continued be	low			

- ~/		
7.06	(continued)	۱

<sup>1</sup> For each additive package introduced into a process stream, specify the compounds
that are present in each additive package, and the concentration of each component.
Assign an additive package number to each additive package and list this number in
column b. (Refer to the instructions for further explanation and an example.
Refer to the glossary for the definition of additive package.)

Additive Package Number		Components Additive Pa	of ckage		Concentration (% or ppm)
1					
				-	
2					
3		•			
				<del>-11.5</del>	
,					
4			· · · · · · · · · · · · · · · · · · ·	<del></del>	
				<del></del>	
5			· · · · · · · · · · · · · · · · · · ·	<del></del>	<u>, , , , , , , , , , , , , , , , , , , </u>
		<del></del>			
Use the follow:	ing codes to	designate how	the concentr	ation was d	etermined:
A = Analytical E = Engineering	result z judgement/a	calculation			
		designate how	the concentr	ation was m	easured:
V = Volume	ing codes to	designate now	the concentr	ac1011 #45 11	cusur cu
W = Weight					

PART	A RESIDUAL TREATMENT PROCESS DESCRIPTION
8.01 CBI	In accordance with the instructions, provide a residual treatment block flow diagram which describes the treatment process used for residuals identified in question 7.01.
	Process type DISPOSA L



BI	type.	(Refer to th	ne instructio	ns for furthe	mplete it sepa r explanation a	and an exampl	e.)
_1	Process	type	<u>N/+</u>				
	а.	b.	с.	d.	е.	f.	g.
	Stream ID Code	Type of Hazardous Waste	Physical State of Residual <sup>2</sup>	Known Compounds <sup>3</sup>	Concentra- tions (% or ppm) <sup>4,5,6</sup>	Other Expected Compounds	Estimated Concen- trations (% or ppm)
	•						
	continue	d balan					

# 8.05 (continued)

<sup>1</sup>Use the following codes to designate the type of hazardous waste:

I = Ignitable

C = Corrosive

R = Reactive

E = EP toxic

T = Toxic

H = Acutely hazardous

<sup>2</sup>Use the following codes to designate the physical state of the residual:

GC = Gas (condensible at ambient temperature and pressure)

GU = Gas (uncondensible at ambient temperature and pressure)

SO = Solid

SY = Sludge or slurry

AL = Aqueous liquid

OL = Organic liquid

IL = Immiscible liquid (specify phases, e.g., 90% water, 10% toluene)

#### 8.05 continued below

8.05 (continued)	8.	05 (	con	tinu	ied)
------------------	----	------	-----	------	------

<sup>3</sup>For each additive package introduced into a process stream, specify the compounds that are present in each additive package, and the concentration of each component. Assign an additive package number to each additive package and list this number in column d. (Refer to the instructions for further explanation and an example. Refer to the glossary for the definition of additive package.)

	Additive Package Number		Components of Additive Package	_	Concentrations (% or ppm)
	1		-	-	·
	2			- -	
	3			<u>.</u>	
				-	
	4				
				-	
	5				
				· · · · · · · · · · · · · · · · · · ·	
	<sup>4</sup> Use the following	g codes to d	esignate how the conce	ntration wa	s determined:
	A = Analytical re E = Engineering	esult judgement/ca	lculation		
.05	continued below			· <b></b>	
]	Mark (X) this box	if you atta	ch a continuation shee	et.	
			56		

8.	n	5	1	^	^	n	t	i	n	11	۵	a	١
υ.	v	,		·	v	11	·	_	11	u	↽	u	,

<sup>5</sup>Use the following codes to designate how the concentration was measured:

V = Volume

W = Weight

<sup>6</sup>Specify the analytical test methods used and their detection limits in the table below. Assign a code to each test method used and list those codes in column e.

Code	<u>Method</u>	Detection Limit (± ug/l)
_1		
2		
_3		
4		
5		
6		

 a.	b.	c.	d.	е.	f.	g.
Stream ID Code	Waste Description Code <sup>1</sup>	Management Method Code <sup>2</sup>	Residual Quantities (kg/yr)	Management of Residual (%) On-Site Off-Site	Costs for Off-Site Management (per kg)	Changes i Managemen Methods
				<del></del>		
1				<del></del>		
 <sup>1</sup> Use the	 e codes provi	.ded in Exhi	bit 8-1 to d	esignate the waste	descriptions	


8.22 CBI	Describe the co (by capacity) your process b	incinerator	s that are us	ed on-site	to burn the r	esiduals ide	argest entified in	
[_]	Combust Chamb Temperatur		oustion namber	Loca Temp	Location of Temperature Monitor		Residence Time In Combustion Chamber (seconds)	
	Incinerator	Primary	Secondary	Primary	Secondary	Primary	Secondary	
	1		<del></del>				-	
	2						-	
	3							
	Yes	ng the app	ropriate resp	onse.	s been submit	• • • • • • • • • • • • • • • • • • • •	1	
8.23 <u>CBI</u> []	Complete the fo are used on-sit treatment block  N/A  Incinerator  1 2	e to burn flow diag	the residuals ram(s). リビステ 尺色 Air Po	identified	t (by capacity in your proce	y) incinerates block or Types Emission Avail	residual of s Data	
	Indicate by circlin	if Office o	of Solid Wasto	e survey has	s been submit	ted in lieu	of response	
	Yes		• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • •	1	
					• • • • • • • • • • • • •			
	Use the following S = Scrubber (if E = Electrostate 0 = Other (special contents)	ng codes t nclude typics precipi	o designate	the air poll				
1	Mark (X) this bo	x if you a	ttach a conti	nuation she	eet.			

2.01 2.81	Mark (X) the appropriate column to indicate whether your company maintains records on the following data elements for hourly and salaried workers. Specify for each data element the year in which you began maintaining records and the number of years the records for that data element are maintained. (Refer to the instructions for further explanation and an example.)									
1	D			Year in Which	Number of					
	Data Element	Hourly Workers	Salaried Workers	Data Collection Began	Years Records Are Maintained					
	Date of hire									
	Age at hire									
	Work history of individual before employment at your facility	-								
	Sex									
	Race		***							
	Job titles									
	Start date for each job title									
	End date for each job title									
	Work area industrial hygiene monitoring data									
	Personal employee monitoring data				-					
	Employee medical history									
	Employee smoking history									
	Accident history									
	Retirement date									
	Termination date									
	Vital status of retirees				,					
	Cause of death data	-14-45-61-41-41-41-41-41-41-41-41-41-41-41-41-41								

.02 BI	In accordance with the in which you engage.	instructions, complete	the following ta	ible for e	ach activity
1	a.	b.	c.	d.	e.
	Activity	Process Category	Yearly Quantity (kg)	Total Workers	Total Worker-Hou
	Manufacture of the	Enclosed			
	listed substance	Controlled Release			
		0pen			_
	On-site use as	Enclosed			
	reactant	Controlled Release		•	
		0pen			
	On-site use as	Enclosed			
	nonreactant	Controlled Release			
		0pen			
	On-site preparation	Enclosed	0.1	1	6
	of products	Controlled Release			
		Open			
		open		-	
	•				

listed substance. BI	s who may potentially come in contact with or be exposed to the
_1	
Labor Category	Descriptive Job Title
A	ELECTRONIC ASSEMBLY
В	
С	
D	
E	
F	
G	
Н	
I	
J	
•	

9.04	In accordance with the instructions indicate associated work areas.	provide your p	process block	flow diagram(s) and
<u>CBI</u>				
[_]	Process type APPLY A	DHESIVE		



9.05	may potentially come additional areas not	work area(s) shown in question 9.04 that encompass workers who in contact with or be exposed to the listed substance. Add ar shown in the process block flow diagram in question 7.01 or question and complete it separately for each process type.
CBI		
_1	Process type	APPLY ADHESIVE
	Work Area ID	Description of Work Areas and Worker Activities
	1	VENTILATED AREA - APPLY MIRDTE OTY
	2	1
	3	
	4	
	5	
	6	
	7	
	8	
	9	· ·
	10	
	<sup>*</sup> .	

9.06 CBI	each labor of come in cont	category at y tact with or	able for each wo our facility tha be exposed to th ly for each prod	it enco ne listo	mpasses worke: ed substance.	s who may pot Photocopy th	tentially
[_]	Process type	e <u>A</u>	PPLY ADH	ESIV	E		
	Work area		• • • • • • • • • • • • • • • • • • • •	• • • • • •	·····		
	Labor Category	Number of Workers Exposed	Mode of Exposu (e.g., dir skin conta	ect	Physical State of Listed Substance	Average Length of Exposure Per Day <sup>2</sup>	Number of Days per Year Exposed
	_A		DIRECT SKIN (	on the	50	A	
					<b>→</b>		
		-					
			-				
			31				
	GC = Gas (or temper included so = Solid  A = 15 minut B = Greater exceedir C = Gas (or temper included so = Solid)	condensible a rature and pruncondensible rature and pruncondensible rature and pruncondes fumes, values fumes, values	essure) e at ambient essure; pors, etc.) to designate ave tes, but not	SY = AL = OL = IL = E = E =	Sludge or sl Aqueous lique Organic lique Immiscible l (specify pha 90% water, 1	urry id id iquid ses, e.g., 0% toluene) sure per day: 2 hours, but ours 4 hours, but	not
_]	Mark (X) this	box if you	attach a continu	uation	sheet.		

9.07	Weighted Average ( Photocopy this que	egory represented in question 9.06 TVA) exposure levels and the 15-mi stion and complete it separately f	nute peak exposure levels.
CBI	area.		
[_]	Process type	APPLY ADHESIVE	
		••••••	
	Labor Category	8-hour TWA Exposure Level (ppm, mg/m³, other-specify)	15-Minute Peak Exposure Leve (ppm, mg/m <sup>3</sup> , other-specify)
	A	_ 1412	
	-		
	-		
			•

80 <u>I</u>	If you monitor worke	r exposur	e to the li	sted substa	nce, compl	ete the fo	llowing table
_]	Sample/Test	Work Area ID	Testing Frequency (per year)	Number of Samples (per test)	Who Samples	Analyzed In-House (Y/N)	Number of Years Record Maintained
	Personal breathing zone		<u> </u>	χρου του τγ	<u> </u>	(1/11)	maintained
	General work area (air)						
	Wipe samples						
	Adhesive patches						
	Blood samples						
	Urine samples						
	Respiratory samples						
	Allergy tests						
	Other (specify)						
	Other (specify)		-			-75-9-14	
	Other (specify)						
	<sup>1</sup> Use the following contact A = Plant industrial B = Insurance carries C = OSHA consultant D = Other (specify)	hygienis		takes the	monitorin	g samples:	

]	Sample Type	<u>s</u>	ampling and Analyti	lytical Methodology					
 )	If you conduct person specify the following				ubstance,				
		•	qpyp-						
1	Equipment Type <sup>1</sup>	Detection Limit <sup>2</sup>	Manufacturer	Averaging Time (hr)	Model Numbe				
	<sup>1</sup> Has the following or								
	Use the following codes to designate personal air monitoring equipment types:  A = Passive dosimeter  B = Detector tube  C = Charcoal filtration tube with pump								
	D = Other (specify) Use the following codes to designate ambient air monitoring equipment types:								
	E = Stationary monitors located within work area F = Stationary monitors located within facility G = Stationary monitors located at plant boundary H = Mobile monitoring equipment (specify) I = Other (specify)								
	<sup>2</sup> Use the following co	des to designate o	detection limit uni	.ts:					
	A = ppm B = Fibers/cubic cen C = Micrograms/cubic	timeter (f/cc) meter (µ/m³)							

Test Descri	ption	(w	eekly,	Frequency monthly, y	y early, etc.
 	<del></del>	 			
 ***************************************		 			

9.12 CBI	Describe the engineering co to the listed substance. P process type and work area.	hotocopy this	ou use to reduce or question and compl	eliminate wor ete it separat	ker exposur ely for eac
[_]	Process type	APPLT	ADHESIVE		
	Work area	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	•	
	Engineering Controls	Used (Y/N)	Year Installed	Upgraded (Y/N)	Year _Upgraded
	Ventilation:				
	Local exhaust	<u>Y</u>	1987	_ N'	
	General dilution				
	Other (specify)				
	Vessel emission controls	-1	<del></del>		
	Mechanical loading or packaging equipment				
	Other (specify)				

com <b>p2</b> 0 co	e it separately for each process type and work	area.							
Process	Process type								
Work are	a								
* .	Equipment or Process Modification	Reduction in Worker Exposure Per Year (%							
***************************************									
		***************************************							
		•							

	Describe the personal protective and safety equi in each work area in order to reduce or eliminat substance. Photocopy this question and complete and work area.	e their exposure	to the listed
CBI	Process type APPLY ADDRESIN	T-	
,	Work area		
	WOLK died	·····	
	Equipment Types  Respirators  Safety goggles/glasses  Face shields  Coveralls  Bib aprons  Chemical-resistant gloves  Other (specify)  VENTILATED ROOTH	Wear or Use (Y/N)  Y Y Y Y Y	

9.15	process respira tested,	ers use respirators when type, the work areas who tors used, the average usend the type and frequere it separately for each	ere the respirat sage, whether or acy of the fit t	ors are us	ed, the type espirators w	of ere fit
CBI						
[_]	Process	type			· · · · · · · · · · · · · · · · · · ·	
	Work Area	Respirator Type	Average Usage	Fit Tested (Y/N)	Type of Fit Test	Frequency of Fit Tests (per year)
		POSITIVE AIR RES	<u>A</u>	N		
						~
	A = Dai B = Wee C = Mor D = Onc	ekly	gnate average u	sage:		
	<sup>2</sup> Use the	following codes to desi	gnate the type	of fit tes	t:	
		alitative antitative				
	3 14	BRAND ORGAN	IC VAPOR	AND	Acib G	AS
	RES	PIRATOR NOS	725 (NIO	IA HZ	PROVED	$\supset$
[_] !	Mark (X)	this box if you attach	a continuation	sheet.		

9.19 <u>CBI</u>	Describe all of the work practices and administrative controls used to reduce or eliminate worker exposure to the listed substance (e.g., restrict entrance only to authorized workers, mark areas with warning signs, insure worker detection and monitoring practices, provide worker training programs, etc.). Photocopy this question and complete it separately for each process type and work area.									
[_]	Process type APPLY ADHESIVE									
	Work area									
	LIMITED A	CCEZZ		7-2-1	····					
	The state of the s									
	Indicate (X) how often you perform each housekeeping task used to clean up routine leaks or spills of the listed substance. Photocopy this question and complete it separately for each process type and work area.  Process type APPLY ADIAESIVE									
.20	leaks or spills of the lisseparately for each process  Process type A P	sted substance. ss type and work PLY ADIAE	Photocopy thi area.	s question an	d complete it					
.20	leaks or spills of the lis separately for each proces	sted substance. ss type and work PLY ADIAE	Photocopy thi area.	s question an	d complete it					
.20	leaks or spills of the lisseparately for each process  Process type A P	sted substance. ss type and work PLY ADIAE	Photocopy thi area.  SIVE  1-2 Times	s question an	More Than 4					
.20	leaks or spills of the lisseparately for each process  Process type A P	sted substance. ss type and work  PLY ADIAE  Less Than	Photocopy thi area.  SIVE  1-2 Times	s question an	More Than 4					
.20	leaks or spills of the lisseparately for each process  Process type A P  Work area	sted substance. ss type and work  PLY ADIAE  Less Than	Photocopy thi area.  SIVE  1-2 Times	s question an	More Than 4					
. 20	leaks or spills of the lisseparately for each process  Process type A P  Work area	sted substance. ss type and work  PLY ADIAE  Less Than	Photocopy thi area.  SIVE  1-2 Times	s question an	More Than 4 Times Per Da					
	leaks or spills of the lisseparately for each process.  Process type A P  Work area	sted substance. ss type and work  PLY ADIAE  Less Than	Photocopy thi area.  SIVE  1-2 Times	s question an	More Than 4					
	leaks or spills of the lisseparately for each process  Process type A P  Work area  Housekeeping Tasks  Sweeping  Vacuuming  Water flushing of floors	sted substance. ss type and work  PLY ADIAE  Less Than	Photocopy thi area.  SIVE  1-2 Times	s question an	More Than 4					
	leaks or spills of the lisseparately for each process  Process type A P  Work area  Housekeeping Tasks  Sweeping  Vacuuming  Water flushing of floors	sted substance. ss type and work  PLY ADIAE  Less Than	Photocopy thi area.  SIVE  1-2 Times	s question an	More Than 4					
. 20	leaks or spills of the lisseparately for each process  Process type A P  Work area  Housekeeping Tasks  Sweeping  Vacuuming  Water flushing of floors	sted substance. ss type and work  PLY ADIAE  Less Than	Photocopy thi area.  SIVE  1-2 Times	s question an	More Than 4					

9.21	Do you have a written medical action plan for responding to routine or emergency exposure to the listed substance?	
	Routine exposure	
	Yes	1
	No	2
	Emergency exposure	
	Yes	1
	No	2
	If yes, where are copies of the plan maintained?	
	Routine exposure:	_
	Emergency exposure:	_
9.22	Do you have a written leak and spill cleanup plan that addresses the listed substance? Circle the appropriate response.	_
	Yes	1
(	No	2
	If yes, where are copies of the plan maintained?	
	Has this plan been coordinated with state or local government response organizations Circle the appropriate response.	
	Yes	1
	No	2
9.23	Who is responsible for monitoring worker safety at your facility? Circle the appropriate response.	
	Plant safety specialist	1
	Insurance carrier	2
	OSHA consultant	3
(	Other (specify) MANAGER OF FACILITIES:	4
		_
[_]	Mark (X) this box if you attach a continuation sheet.	

### SECTION 10 ENVIRONMENTAL RELEASE

#### General Instructions:

Complete Part E (questions 10.23-10.35) for each non-routine release involving the listed substance that occurred during the reporting year. Report on all releases that are equal to or greater than the listed substance's reportable quantity value, RQ, unless the release is federally permitted as defined in 42 U.S.C. 9601, or is specifically excluded under the definition of release as defined in 40 CFR 302.3(22). Reportable quantities are codified in 40 CFR Part 302. If the listed substance is not a hazardous substance under the Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) and, thus, does not have an RQ, then report releases that exceed 2,270 kg. If such a substance however, is designated as a CERCLA hazardous substance, then report those releases that are equal to or greater than the RQ. The facility may have answered these questions or similar questions under the Agency's Accidental Release Information Program and may already have this information readily available. Assign a number to each release and use this number throughout this part to identify the release. Releases over more than a 24-hour period are not single releases, i.e., the release of a chemical substance equal to or greater than an RQ must be reported as a separate release for each 24-hour period the release exceeds the RQ.

For questions 10.25-10.35, answer the questions for each release identified in question 10.23. Photocopy these questions and complete them separately for each release.

10.01	Where is your facility located? Circle all appropriate responses.
CBI	
[_]	Industrial area
	Urban area
	Residential area
	Agricultural area
	Rural area
	Adjacent to a park or a recreational area
	Within 1 mile of a navigable waterway
	Within 1 mile of a school, university, hospital, or nursing home facility 8
	Within 1 mile of a non-navigable waterway
	Other (specify)10

	Specify the exact location of your facility (from central point where process unit is located) in terms of latitude and longitude or Universal Transverse Mercader (UTM) coordinates.							
	Latitude		28 . (	<i>O'</i> "				
	Longitude	•••••	82.0	,				
	UTM coordinates Zon	e, North	ing, Ea	asting				
10.03	If you monitor meteorological co the following information.	nditions in the vicin	ity of your faci	lity, provide				
	Average annual precipitation	•••••		inches/year				
	Predominant wind direction							
10.04	Indicate the depth to groundwate	r holov vour facility						
10.04	6-1	•						
	Depth to groundwater	***************************************	,	meters				
10.05 CBI	For each on-site activity listed, indicate (Y/N/NA) all routine releases of the listed substance to the environment. (Refer to the instructions for a definition of Y, N, and NA.)							
	listed substance to the environment	, indicate (Y/N/NA) a ent. (Refer to the i	ll routine releanstructions for	ises of the a definition of				
CBI	listed substance to the environmer Y, N, and NA.)	ent. (Refer to the in Env	nstructions for ironmental Relea	a definition of				
CBI	listed substance to the environme Y, N, and NA.)  On-Site Activity	ent. (Refer to the in	nstructions for	a definition of				
CBI	listed substance to the environme Y, N, and NA.)  On-Site Activity  Manufacturing	ent. (Refer to the in Env	nstructions for ironmental Relea	a definition of				
CBI	listed substance to the environme Y, N, and NA.)  On-Site Activity  Manufacturing  Importing	ent. (Refer to the in Env	nstructions for ironmental Relea	a definition of				
CBI	listed substance to the environme Y, N, and NA.)  On-Site Activity  Manufacturing	ent. (Refer to the in Env	nstructions for ironmental Relea	a definition of				
CBI	listed substance to the environme Y, N, and NA.)  On-Site Activity  Manufacturing  Importing	ent. (Refer to the in Env.	ironmental Relea	a definition of				
CBI	listed substance to the environme Y, N, and NA.)  On-Site Activity  Manufacturing  Importing  Processing	ent. (Refer to the in Env.	ironmental Relea	a definition of				
CBI	listed substance to the environme Y, N, and NA.)  On-Site Activity  Manufacturing  Importing  Processing  Otherwise used	ent. (Refer to the in Env.	ironmental Relea	a definition of				
CBI	listed substance to the environme Y, N, and NA.)  On-Site Activity  Manufacturing  Importing  Processing  Otherwise used  Product or residual storage	ent. (Refer to the in Env.	ironmental Relea	a definition of				
CBI	listed substance to the environment Y, N, and NA.)  On-Site Activity  Manufacturing  Importing  Processing  Otherwise used  Product or residual storage  Disposal	ent. (Refer to the in Env.	ironmental Relea	a definition of				
CBI	listed substance to the environment Y, N, and NA.)  On-Site Activity  Manufacturing  Importing  Processing  Otherwise used  Product or residual storage  Disposal	ent. (Refer to the in Env.	ironmental Relea	a definition of				
10.05 <u>CBI</u> [ _ ]	listed substance to the environment Y, N, and NA.)  On-Site Activity  Manufacturing  Importing  Processing  Otherwise used  Product or residual storage  Disposal	ent. (Refer to the in Env.	ironmental Relea	a definition of				

Process ty	pe <u>.</u>	APPLY	ADHESIVE		
<b>C b</b> · · · · · · · · · · · · · · · · · · ·	TD Code				n . ncc: :
	ID Code		ontrol Technology		Percent Efficien
8.1		10 1	A		NIA
				····	
-					
					<u> </u>
	<del> </del>			<del></del>	
			·// <del>=====</del>		•
	<del></del>				
÷					

10.09 CBI	Point Source Emissions Identify each emission point source containing the listed substance in terms of a Stream ID Code as identified in your process block or residual treatment block flow diagram(s), and provide a description of each point source. Do not include raw material and product storage vents, or fugitive emission sources (e.g., equipment leaks). Photocopy this question and complete it separately for each process type.						
	Process type		APPLY	ADHES	<b>' / E</b>		
	Point Source ID Code			Descriptio	n of Emission Po	int Source	
	8.1			NIN			
-							
-			-				
-							
-							
-							
-			<del></del>			· · · · · · · · · · · · · · · · · · ·	
_							
			<del></del>				
			÷				
	· ·						

Mark (X)

this

ьoх

Point	y completin		ng rapte.			Maximum	de identified  Maximum Emission	Maximum
Source ID Code	Physical State	Average Emissions (kg/day)	Frequency <sup>2</sup> (days/yr)	Duration <sup>3</sup> (min/day)	Average Emission Factor	Emission Rate (kg/min)	Rate Frequency (events/yr)	Emission Rate Duration (min/even
8_1	4/4	NIN	9/14	N/A	N/A	A/N	N/A	N/A
<del></del> -								
<sup>1</sup> Use the G = Gas	e following s; V = Vapor	codes to desi	gnate physica ulate; A = Aero	l state at the osol; $0 = 0$ the	e point of re er (specify)	lease:		
<sup>2</sup> Frequer	ncy of emiss	sion at any le	evel of emission	on				
3 Duratio	on of emissi	on at any lev	el of emission	า				

Point Source ID Code	Stack Height(m)	Stack Inner Diameter (at outlet)	Exhaust Temperature (°C)	Emission Exit Velocity (m/sec)	Building Height(m)	Building Width(m)	
8,1	N/A	N/A	N/A	AlA	NA	<u> </u>	1
				-			_
					-		
							_
						·	_
· · · · · · · · · · · · · · · · · · ·							_
						-	_
							-
·							_
<sup>2</sup> Width of		or adjacent r adjacent b					
<sup>3</sup> Use the :	following c	odes to desi	gnate vent t	ype:			
H = Hori: V = Vert:							
		•					

.2	If the listed substance is emi distribution for each Point Sor Photocopy this question and con	urce ID Code id	dentified in question 10.09. rately for each emission point	
	Point source ID code		B.(	
	Size Range (microns)		Mass Fraction (% ± % preci	sio
	< 1		NA	
	≥ 1 to < 10			
	≥ 10 to < 30			
	≥ 30 to < 50			
	≥ 50 to < 100			
	≥ 100 to < 500			
	≥ 500			
			Total = 100%	
			•	
			·	

							<del></del>
10.13 CBI	Equipment Leaks Complete types listed which are expactording to the specified the component. Do this for residual treatment block for exposed to the listed process, give an overall process to the listed substor each process type.	osed to the l weight perces r each proces low diagram(s substance. I ercentage of	isted suent of the stype is type is the stype is the styp	bstance a e listed dentified ot includ s a batch year tha	nd which a substance in your a e equipment or interment t the pro-	are in ser passing process b nt types mittently cess type	rvice through lock or that are operated
	· · · · · · · · · · · · · · · · · · ·	<b></b>					
[_]	Process type App	HOU FIL	SIVE				
	Percentage of time per year	r that the li	sted sub	stance is	exposed	to this p	cocess
	type	• • • • • • • • • • • • •	• • • • • • • •	• • • • • • • •	• • • • • • • •		
	N/A		of Compo of Lister	nents in : d Substan	Service by ce in Pro	y Weight I cess Strea	Percent am
	Equipment Type	Less than 5%	5-10%	11_259	26-75%	76 00%	Greater
	Pump seals <sup>1</sup>	Chan 3/6	3-10%	11-23%	20-73%	70-99%	than 99%
	Packed						
	Mechanical						<del></del>
	Double mechanical <sup>2</sup>			and the same of th			
	Double mechanical <sup>2</sup> Compressor seals <sup>1</sup>						
	Compressor seals <sup>1</sup>						
	Compressor seals <sup>1</sup> Flanges						
	Compressor seals <sup>1</sup> Flanges Valves						
	Compressor seals <sup>1</sup> Flanges Valves Gas <sup>3</sup>						
	Compressor seals <sup>1</sup> Flanges Valves Gas <sup>3</sup> Liquid Pressure relief devices <sup>4</sup>						
	Compressor seals <sup>1</sup> Flanges Valves Gas <sup>3</sup> Liquid Pressure relief devices <sup>4</sup> (Gas or vapor only)						

<sup>1</sup>List the number of pump and compressor seals, rather than the number of pumps or compressors

10.13 continued on next page

Gas Liquid

	Mark	(X)	this	box	if	you	attach	а	continuation	sheet
--	------	-----	------	-----	----	-----	--------	---	--------------	-------

*If double mechanical seals are operated with the barrier (B) fluid at a pressure greater than the pump stuffing box pressure and/or equipped with a sensor (S) the vith a "B" and/or an "S", respectively  *It detect failure of the seal system, the barrier fluid system, or both, indivitin a "B" and/or an "S", respectively  *Conditions existing in the valve during normal operation  *Report all pressure relief devices in service, including those equipped with control devices  *Lines closed during normal operation that would be used during maintenance operations  10.14 Pressure Relief Devices with Controls Complete the following table for those pressure relief devices in service are controlled. If a pressure relief device in not controlled enter "None" under column c.    Nimber of Percent Chemical   Estimated Pressure Relief Devices   Percent Chemical   Estimated Pressure Relief Devices   In Vessel   Control Device   Control Efficient	10.13	(continued)			
*Report all pressure relief devices in service, including those equipped with control devices  *Lines closed during normal operation that would be used during maintenance operations  10.14 Pressure Relief Devices with Controls Complete the following table for those pressure relief devices is nearly are controlled. If a pressure relief device is not controlled enter "None" under column c.    N		greater than the pump str will detect failure of the	uffing box pressure : he seal system, the	and/or equipped wi	th a sensor (S) that
SLines closed during normal operation that would be used during maintenance operations  10.14 Pressure Relief Devices with Controls Complete the following table for those pressure relief devices identified in 10.13 to indicate which pressure relief devices in service are controlled. If a pressure relief device is not controlled enter "None" under column c.		<sup>3</sup> Conditions existing in th	he valve during norm	al operation	
10.14 Pressure Relief Devices with Controls Complete the following table for those pressure relief devices identified in 10.13 to indicate which pressure relief devices in service are controlled. If a pressure relief device is not controlled enter "None" under column c.    N		<sup>4</sup> Report all pressure relie control devices	ef devices in servic	e, including those	equipped with
pressure relief devices identified in 10.13 to indicate which pressure relief devices in service are controlled. If a pressure relief device is not controlled enter "None" under column c.		<sup>5</sup> Lines closed during norma operations	al operation that wo	uld be used during	maintenance
Number of Percent Chemical in Vessel Control Device Control Efficier  1 Refer to the table in question 10.13 and record the percent range given under the heading entitled "Number of Components in Service by Weight Percent of Listed Substance" (e.g., <5%, 5-10%, 11-25%, etc.)  2 The EPA assigns a control efficiency of 100 percent for equipment leaks controlle with rupture discs under normal operating conditions. The EPA assigns a control efficiency of 98 percent for emissions routed to a flare under normal operating conditions	CBI	pressure relief devices in devices in service are con enter "None" under column	dentified in 10.13 to atrolled. If a press	indicate which n	ressure relief
Pressure Relief Devices in Vessel Control Device Control Efficient  Refer to the table in question 10.13 and record the percent range given under the heading entitled "Number of Components in Service by Weight Percent of Listed Substance" (e.g., <5%, 5-10%, 11-25%, etc.)  The EPA assigns a control efficiency of 100 percent for equipment leaks control with rupture discs under normal operating conditions. The EPA assigns a control efficiency of 98 percent for emissions routed to a flare under normal operating conditions	· ·	· a.	<u> </u>	c.	<del>-</del>
Substance" (e.g., <5%, 5-10%, 11-25%, etc.)  The EPA assigns a control efficiency of 100 percent for equipment leaks controlle with rupture discs under normal operating conditions. The EPA assigns a control efficiency of 98 percent for emissions routed to a flare under normal operating conditions				Control Device	Estimated Control Efficiency <sup>2</sup>
Substance" (e.g., <5%, 5-10%, 11-25%, etc.)  The EPA assigns a control efficiency of 100 percent for equipment leaks controlle with rupture discs under normal operating conditions. The EPA assigns a control efficiency of 98 percent for emissions routed to a flare under normal operating conditions			•		
Substance" (e.g., <5%, 5-10%, 11-25%, etc.)  The EPA assigns a control efficiency of 100 percent for equipment leaks controlle with rupture discs under normal operating conditions. The EPA assigns a control efficiency of 98 percent for emissions routed to a flare under normal operating conditions					
Substance" (e.g., <5%, 5-10%, 11-25%, etc.)  The EPA assigns a control efficiency of 100 percent for equipment leaks controlle with rupture discs under normal operating conditions. The EPA assigns a control efficiency of 98 percent for emissions routed to a flare under normal operating conditions					
Substance" (e.g., <5%, 5-10%, 11-25%, etc.)  The EPA assigns a control efficiency of 100 percent for equipment leaks controlle with rupture discs under normal operating conditions. The EPA assigns a control efficiency of 98 percent for emissions routed to a flare under normal operating conditions					
Substance" (e.g., <5%, 5-10%, 11-25%, etc.)  The EPA assigns a control efficiency of 100 percent for equipment leaks controlle with rupture discs under normal operating conditions. The EPA assigns a control efficiency of 98 percent for emissions routed to a flare under normal operating conditions	,				
Substance" (e.g., <5%, 5-10%, 11-25%, etc.)  The EPA assigns a control efficiency of 100 percent for equipment leaks controlle with rupture discs under normal operating conditions. The EPA assigns a control efficiency of 98 percent for emissions routed to a flare under normal operating conditions					***
Substance" (e.g., <5%, 5-10%, 11-25%, etc.)  The EPA assigns a control efficiency of 100 percent for equipment leaks controlle with rupture discs under normal operating conditions. The EPA assigns a control efficiency of 98 percent for emissions routed to a flare under normal operating conditions					
Substance" (e.g., <5%, 5-10%, 11-25%, etc.)  The EPA assigns a control efficiency of 100 percent for equipment leaks controlle with rupture discs under normal operating conditions. The EPA assigns a control efficiency of 98 percent for emissions routed to a flare under normal operating conditions					
Substance" (e.g., <5%, 5-10%, 11-25%, etc.)  The EPA assigns a control efficiency of 100 percent for equipment leaks controlle with rupture discs under normal operating conditions. The EPA assigns a control efficiency of 98 percent for emissions routed to a flare under normal operating conditions					***
Substance" (e.g., <5%, 5-10%, 11-25%, etc.)  The EPA assigns a control efficiency of 100 percent for equipment leaks controlle with rupture discs under normal operating conditions. The EPA assigns a control efficiency of 98 percent for emissions routed to a flare under normal operating conditions					
Substance" (e.g., <5%, 5-10%, 11-25%, etc.)  The EPA assigns a control efficiency of 100 percent for equipment leaks controlle with rupture discs under normal operating conditions. The EPA assigns a control efficiency of 98 percent for emissions routed to a flare under normal operating conditions					
efficiency of 98 percent for emissions routed to a flare under normal operating conditions	ı	neading entitled "Number o	I Components in Serv	d the percent ranging to the percent range of the p	ge given under the cent of Listed
[_] Mark (X) this box if you attach a continuation sheet.		efficiency of 98 percent for	ormal operating cond	litions. The EPA a	assigns a control
	[ <u>]</u> ] M	ark (X) this box if you at	tach a continuation	sheet.	

pment Type seals cked chanical uble mechanical	Leak Detection Concentration (ppm or mg/m³) Measured at Inches from Source	Detection Device	Frequency of Leak Detection		Repairs Completed (days afte
pment Type seals cked chanical uble mechanical	(ppm or mg/m³) Measured atInches		of Leak Detection	Initiated (days after	Completed (days afte
cked chanical uble mechanical					
cked chanical uble mechanical					
chanical uble mechanical	4-4				
uble mechanical	<del></del>				
		<del></del>			
ressor seals					
ges					-
es -	· · · · · · · · · · · · · · · · · · ·				
3					
- quid					1 1
sure relief vices (gas vapor only)				amagina (p.,	- The state of the
e connections					
<b>S</b>					
uid _					
ended lines				•	
<b>.</b>					
uid					
_					
	quid sure relief vices (gas vapor only) e connections quid ended lines uid the following co	quid sure relief vices (gas vapor only) e connections quid ended lines uid the following codes to designate of	quid sure relief vices (gas vapor only) Le connections quid ended lines	quid sure relief vices (gas vapor only) e connections quid ended lines  uid  the following codes to designate detection device:	quid sure relief vices (gas vapor only) e connections quid ended lines

Mark	<u> </u>	N/			flow diagram	•				Operat-	-				
		ζ '		Composition	Throughput	Vessel	Vessel Filling	Vessel Inner	Unnel	ing	173	ъ .	••		
(X)		Vessel	Roof	of Stored	(liters						Vessel Emission	Design Flow	Vent Diameter	Control Efficiency	Basis for
thi	İ	Type <sup>*</sup>	Seals'	Materials'	per year)	(gpm)	(min)	<u>(m)</u>	<u>(m)</u>		Controls <sup>4</sup>		(cm)	(%)	Estimate
.s d															
ŏ										<del></del>					
i.												<del></del>			
you															
u a															
tta															
ch				· · · · · · · · · · · · · · · · · · ·											
a C					- Re-										
on															
nt															
Ċ.													<b>-</b>		
tinuat		<sup>1</sup> Use th	he follow	ing codes to	designate ve	essel type		<sup>2</sup> Use	the fo	llowing	codes to	designa	te floatin	g roof seal	 s:
tinua		F =	= Fixed ro	oof		essel type	 	MS1	= Med	hanical	shoe, pri	mary	te floatin	g roof seal	 s:
tinuation sh		F :	= Fixed ro = Contact	oof internal flo	nating roof			MS1 MS2	= Med = Sho	hanical e-mount	shoe, pri ed seconda	mary ry	te floatin	g roof seal	 s:
tinuation shee		F = CIF = NCIF = EFR =	= Fixed ro = Contact = Nonconta = External	oof internal flo act internal l floating ro	nating roof floating roo oof	of		MS1 MS2 MS2 LM1	= Mecl = Shoo R = Rim = Liq	hanical e-mounte -mounte uid-mou	shoe, pri ed seconda d, seconda nted resil	mary ry ry		-	·
tinuation she		F = CIF = NCIF = EFR =	= Fixed ro = Contact = Nonconta = External = Pressure	oof internal flo act internal l floating ro e vessel (ind	nating roof floating roo	of		MS1 MS2 MS2 LM1 LM2	= Mecl = Shoo R = Rim = Liqu = Rim	hanical e-mounte -mounte uid-moun -mounte	shoe, pri ed seconda d, seconda nted resil d shield	mary ry ry		-	·
tinuation shee		F = CIF = NCIF = EFR = P = H	= Fixed ro = Contact = Nonconta = External	oof internal floact internal l floating ro e vessel (inc	nating roof floating roo oof	of		MS1 MS2 MS21 LM1 LM2 LMW	= Med = Shook R = Rim = Liqu = Rim = Wea	hanical e-mounte -mounte uid-mounte -mounte ther sh	shoe, pri ed seconda d, seconda nted resil d shield	mary ry ry ient fi	lled seal,	primary	
tinuation shee		F = CIF = NCIF = EFR = P = H	= Fixed ro = Contact = Nonconta = External = Pressure = Horizon	oof internal floact internal l floating ro e vessel (inc	nating roof floating roo oof	of		MS1 MS2 MS2 LM1 LM2 LMW VM1 VM2	= Mecl = Sho R = Rim = Liq = Rim = Wea = Vap = Rim	hanical e-mounte -mounte uid-mounte ther shi or mounte -mounte	shoe, prined secondari, secondarited resilicield ted resilicield secondary	mary ry ry ient fil	lled seal,	primary	 s:
tinuation shee		F = CIF = NCIF = EFR = P = U =	= Fixed ro = Contact = Nonconta = External = Pressuro = Horizon = Undergro	oof internal floact internal l floating re e vessel (inc tal ound	nating roof floating roo nof dicate pressu	of are rating	g)	MS1 MS2 MS2 LM1 LM2 LMW VM1 VM2 VMW	= Mecl = Shoo R = Rim = Liq = Rim = Wea = Vap = Rim = Wea	hanical e-mounte mounte uid-mounte ther sh e-mounte ther sh	shoe, prined secondari, secondarited resilidited resilidited resilidisecondarield	mary ry ient fil	lled seal, led seal,	primary primary	 s:
tinuation shee		F = CIF = NCIF = EFR = U = U = 3	= Fixed ro = Contact = Nonconta = External = Pressure = Horizon = Undergro	oof internal floact internal l floating ro e vessel (included) tal ound	nating roof floating roo oof	of are rating	g)	MS1 MS2 MS2 LM1 LM2 LMW VM1 VM2 VMW	= Mecl = Shoo R = Rim = Liq = Rim = Wea = Vap = Rim = Wea	hanical e-mounte mounte uid-mounte ther sh e-mounte ther sh	shoe, prined secondari, secondarited resilidited resilidited resilidisecondarield	mary ry ient fil	lled seal, led seal,	primary primary	 s:
tinuation shee		F = CIF = NCIF = EFR = U = U = 13 Indicate	= Fixed ro = Contact = Nonconta = External = Pressure = Horizon = Undergro ate weigh	internal floact internal floact internal floating roe vessel (inctal ound)	nating roof floating roo nof dicate pressu	of are rating substance	g) . Include	MS1 MS2 MS2 LM1 LM2 LMW VM1 VM2 VMW2	= Mecl = Sho R = Rim = Liq = Rim = Wea = Vap = Rim = Wea	hanical e-mounte -mounte uid-mounte ther sh or mount -mounte ther sh ile orga	shoe, pried seconda d, seconda nted resil d shield ield ted resili d secondar ield	mary ry ient fil ent fill y	lled seal, led seal,	primary primary	s:
tinuation shee		F = CIF = NCIF = EFR = U = 3 Indica 4 Other 5 Gas/va	= Fixed ro = Contact = Nonconta = External = Pressure = Horizon = Undergro ate weigh than flow	internal floact internal floact internal floating relevant evessel (incommoder percent of ating roofs rate the emission of the control of the	nating roof floating roo pof dicate pressu the listed s	of are rating substance ol device	g) . Include was desig	MS1 MS2 MS2 LM1 LM2 LMW VM1 VM2 VMW the total	= Mecl = Shook R = Rim = Liq = Rim = Wea = Vap = Rim = Wea l volation	hanical e-mounte mounte ther shi or mounte ther shi ile orga	shoe, pried seconda d, seconda nted resil d shield ield ted resili d secondar ield	mary ry ient fil ent fill y	lled seal, led seal,	primary primary	 s:
tinuation shee		F = CIF = NCIF = EFR = U = 3 Indica 4 Other 5 Gas/va 6 Use the	= Fixed ro = Contact = Nonconta = External = Pressure = Horizon = Undergro ate weigh than flow	internal floact internal floact internal floating role vessel (included to percent of ating roofs rate the eming codes to	nating roof floating roo nof dicate pressu	of are rating substance ol device	g) . Include was desig	MS1 MS2 MS2 LM1 LM2 LMW VM1 VM2 VMW the total	= Mecl = Shook R = Rim = Liq = Rim = Wea = Vap = Rim = Wea l volation	hanical e-mounte mounte ther shi or mounte ther shi ile orga	shoe, pried seconda d, seconda nted resil d shield ield ted resili d secondar ield	mary ry ient fil ent fill y	lled seal, led seal,	primary primary	 s:

PART	E	NON-ROUTINE	RELEASES
1 127/1	-	TACM-VOOTTIAD	KEDEROES

	(N)A		Date	Time	Date	Time
	Release	-	Started	(am/pm)	Stopped	(am/pm)
	1					
	2	-	<del></del>			
	3	_				
	4		A STATE OF THE STA			
	5	_				
	6	_				-
10.24	Specify th	ne weather o	anditions at the	time of each :	1	
10.24	Specify (	ie weather c	onditions at the	time of each i	release.	
	Release	Wind Speed (km/hr)	Wind Direction	Humidity (%)	Temperature (°C)	Precipitation (Y/N)
	1	•				<del></del>
	2					
	2 3 4 5					
	2 3 4 5					
	2 3 4 5					
	2 3 4 5					
	2 3 4 5					
	2 3 4 5					

DBA Systems, Inc. P.O. Box 550 Melbourne, FL 32902-0550

ATTN: Gary Perkins

TSCA Document Processing Center (TS-790)
Office of Toxic Substances
U.S. Environmental Protection Agency
Room L-100
401 M Street, S.W.
Washington, D.C. 20460
ATTN: CAIR Reporting

